



## KLX DISSOLVABLE FRAC PLUG

The KLX Dissolvable Frac Plug provides a practical zonal isolation solution for extended reach horizontal wellbores, refracs and other zonal isolation applications where challenging mill-out situations are present.

The KLX Dissolvable Frac Plug can also be retrofitted to be run with a ball in place option. This option requires only the replacing of the lower guide and tension mandrel. The ball in place option currently is available on the 4.5", 5" and 5.5" sizes.

The plug is composed of proprietary magnesium alloy, which dissolves in the presence of salinity in wellbore fluids and temperature. This reduces cost incurred with composite plugs and any mill out restrictions. In addition, it decreases fluid costs trying to bring mill-up returns back to surface.



### FEATURES & BENEFITS

- Predictable Dissolution Times Based on Salinity and Temperature Variables
- No Mill Out Required to Remove Plug, Saving Rig Time and Cost
- Sets with Industry Standard Pressure Setting Tools
- Large Bore Size—Resulting in Higher Flow Back and Faster Dissolution
- 10,000psi Differentially Rated and Tested
- Temperature Range: 80°F to 275°F

### PRODUCT SPECIFICATIONS

TOOL SIZE (IN)	CSG WEIGHT RANGE (#)	MIN CSG ID (IN)	MAX CSG ID (IN)	PLUG ID (IN)	BALL OD (IN)	PLUG OD (IN)	LENGTH (IN)	KLX PN
3.500"	9.2#	2.918"	3.046"	1.050"	1.875"	2.690"	8.40"	DSV-35-FPH
4.000"	11#	3.402"	3.530"		2.500"	3.230"	9.59"	DSV-40-FPH
4.500"	13.5# PATCH	3.321"			1.875"	3.050"	8.28"	DSV-45-PPH
	11.6# - 13.5#	3.853"	4.069"	2.750"	3.670"	9.58"	DSV-45-FPH	
	15.1#	3.750"	3.903"		3.600"	9.53"	DSV-46-FPH	
5.000"	18#	4.195"	4.361"		4.026"	10.04"	DSV-50-FPH	
	21.4#	4.030"	4.218"	3.875"	10.23"	DSV-52-FPH		
5.500"	17# - 20#	4.695"	4.976"	1.790"	4.570"	9.53"	DSV-55-FPH	
	20# - 23#	4.578"	4.868"		4.375"	9.57"	DSV-56-FPH	
	23# - 26.8#	4.393"	4.766"		4.300"	9.59"	DSV-57-FPH	



3040 Post Oak Blvd., 15th Floor  
 Houston, TX 77056  
 Tel 832.844.1015  
[klxenergy.com](http://klxenergy.com)

NEXT LEVEL READINESS >